



ULTRACORE QUICK-FIX CONNECTORS Specification Sheet		
Part Number	Description	Length
FOR 7/8" O.D. COPPER		
WCC-109-PP	3/4" I.D. Compression Coupling	9"
WCC-112-PP	x 3/4" I.D. Compression Coupling	12"
FOR 5/8" O.D. COPPER		
WCC-509-PP	1/2" I.D. Compression Coupling	9"
WCC-512-PP	x 1/2" I.D. Compression Coupling	12"

DESIGN FEATURES

- Frozen or cracked pipes can be fixed in minutes
- Exclusive POWR-TIGHT 12-point crimp-many times industry standard
- Chloramine resistant tubing
- Withstands dramatic changes in water pressure
- Easy installation, no special tools or soldering required.

MATERIAL SPECIFICATIONS

- Working Pressure: 160 psi
- Operating Temperature: 33° F - 140° F
- Tubing: Reinforced PVC, NSF 61 Compliant
- Nuts & End Fittings: Brass
- Washers: NSF 61 Compliant

COMPLIANCES/LISTINGS

- IAPMO Certified
- NSF Compliant
- ASME A112.18.6



3689 Arrowhead Drive, Carson City, NV 89706
 Phone (800) 854-3215 Fax (800) 243-1777
 E-mail sales@lspproducts.com Website www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

AF/S-2004 (04-08) Rev 3

Product Submittal	
Job Name	
Date	
Part Number	Quantity
Architect	
Contractor	